



Innovative

Quality

Service

M K ASSOCIATES

SPECIALIST IN CASHEWS MACHINERY

MANUFACTURERS OF MACHINERY SALE & SERVICE

☎ M. : 9879041476

📍 31, Meladi Estate, Gota, Ahmedabad - 382481.

✉ hkmaikal@gmail.com • hk_maikal123@yahoo.com

🌐 www.cashewsmachinemk.in



Cashew Shelling Machine



M K ASSOCIATES

CSM - 400

Specification :

- ❖ Capacity : 350 - 400 kg/hr. RCN
- ❖ Dimension : L 9.0 X W 4.0 X H 5.0 (m)
- ❖ Whole Kernels percentage: 80% - 90%
- ❖ Broken Rate : 2% - 4%
- ❖ Power Consumption : 12 KWh
- ❖ Power Supply : 3 phase 440V-50 Hz
- ❖ Working parts material by S.S. 304 & Machine Structure Material by M.S.
- ❖ The Machine is controlled by PLC Programmer.
- ❖ Control Functions and running parameters are displayed on the touch screen 7-inch.



Use Cashew Sheling Machine sut our Provides more Efficient

- Reduced 85-90% labor in cutting Step.
- Increase productivity.
- Higher percent of kernels.
- Low percent of broken and piece nuts.
- Improving the work environment
- Simple to use, easy to operate.
- One operator
- To achieved high economic cost of low investment, low production costs...

Cashew Shelling Machine



M K ASSOCIATES

CSM - 600

Specification :

- ❖ Capacity : 550-600kg/hr.RCN
- ❖ Dimension : L 15 x W 5.0 x H 5.0 (m)
- ❖ Whole Kernels percentage: 85% - 95%
- ❖ Broken percentage : 1-5% - Nuts sizes
- ❖ Power Consumption : 17 KWh
- ❖ Power Supply : 3 phase 440V-50 Hz
- ❖ Working parts material by S.S. 304 & Machine Structure Material by S.S.
- ❖ The Machine is controlled by PLC Programmer.
- ❖ Control Functions and running parameters are displayed on the touch screen 7-inch.



Use Cashew Sheling Machine sut our Provides more Efficient

- Reduced 85-90% labor in cutting Step.
- Increase productivity.
- Higher percent of kernels.
- Low percent of broken and piece nuts.
- Improving the work environment
- Simple to use, easy to operate.
- One operator
- To achieved high economic cost of low investment, low production costs...

Cashew Shelling Machine



M K ASSOCIATES

CSM - 800

Specification:

- ❖ Capacity : 800 - 900 kg/hr. RCN
- ❖ Dimension : L 13.0 X W 4.0 X H 5.0 (m)
- ❖ Whole Kernels percentage: 80% - 90%
- ❖ Broken Rate : 2% - 4%
- ❖ Power Consumption : 20 KWh
- ❖ Power Supply : 3 phase 440V-50 Hz
- ❖ Working parts material by S.S. 304 & Machine Structure Material by M.S.
- ❖ The Machine is controlled by PLC Programmer.
- ❖ Control Functions and running parameters are displayed on the touch screen 7-inch.



CSM - 200

Specification :

- ❖ Capacity : 180 - 200 kg/hr. RCN
- ❖ Dimension : L 6.0 X W 3.0 X H 4.0 (m)
- ❖ Whole Kernels percentage: 80% - 90%
- ❖ Broken Rate : 2% - 4%
- ❖ Power Consumption : 6 KWh
- ❖ Power Supply : 3 phase 440V-50 Hz
- ❖ Working parts material by S.S. 304 & Machine Structure Material by M.S.
- ❖ The Machine is controlled by PLC Programmer.
- ❖ Control Functions and running parameters are displayed on the touch screen 7-inch.

Cashew Shelling Machine



M K ASSOCIATES

CSM - 1200

Specification :

- ❖ Capacity : 1100-1200kg/hr.RCN
- ❖ Dimension : L 17 x W 6.0 x H 5.0 (m)
- ❖ Whole Kernels percentage: 85% - 95%
- ❖ Broken percentage : 1-5% - Nuts sizes
- ❖ Power Consumption : 24 KWh
- ❖ Power Supply : 3 phase 440V-50 Hz
- ❖ Working parts material by S.S. 304 & Machine Structure Material by S.S.
- ❖ The Machine is controlled by PLC Programmer.
- ❖ Control Functions and running parameters are displayed on the touch screen 7-inch.



Raw Cashew Grading Machine



M K ASSOCIATES

RCNS - 1500

Specification :

- Capacity : 1500 - 1800 kg/hr.
- Dimension : L 15.0 X W 2.0 X H 3.0 (m)
- Power Consumption: 3KWh
- Power Supply : 3 Phase 440v-50Wz
- Mesh Thickness : 4mm
- RCN Sizes : A+, A, B, C, D, E

RCNS - 1000

Specification :

- Capacity : 800 - 1000 kg/hr.
- Dimension : L 15.0 X W 1.8 X H 2.6 (m)
- Power Consumption: 3KWh
- Power Supply : 3 Phase 440v-50Wz
- Mesh Thickness : 4mm
- RCN Sizes : A+, A, B, C, D, E



AUTOMATIC WALNUT SHELLING LINE MACHINE



M K ASSOCIATES

WSL - 600

Specification

- Capacity: 500-600kg Nuts/hour
- After shelling, walnut will be separated from shell.
- Shelling Line Size : L9m x W3m x H4m
- Powersupply : 3 Phases 440V - 50Hz
- Power consumption : 10 HP
- Control panel's electric spare part : Schneider



AUTOMATIC WALNUT SHELLING LINE MACHINE



M K ASSOCIATES

WSL - 600

Specification :

- ❖ Capacity : 55-600kg Nuts/hour
- ❖ Dimension : L 9m x W 3m x H 4m
- ❖ Whole Kernels percentage: 85% - 95%
- ❖ Broken percentage : 1-5% - Nuts sizes
- ❖ Power Consumption : 10 KWh
- ❖ Power Supply : 3 phase 440V-50 Hz
- ❖ Working parts material by S.S. 304 & Machine Structure Material by S.S.
- ❖ The Machine is controlled by PLC Programmer.
- ❖ Control Functions and running parameters are displayed on the touch screen 7-inch.

